



TECHNICAL SPECIFICATIONS								
Max working negative pressure		Pa		20000				
Working temperature		°C		-10<T<60				
Electric control panel feeding		230 V AC 50Hz						
Cartridges cleaning system		pulse-set						
Compressed air tank working pressure		bar		5				
DIMENSIONS								
Model	Filtering surface	Number of filtering elements	Number of cleaning valves	Compressed air consumption	A	H Tot	Ø In	Ø Out
	[m ²]	[-]	[-]	[Nl/activ]	[mm]	[mm]	[mm]	[mm]
CNSB145-02X0207	10	4	2	87	650	2600	120	150
CNSB145-02X0210	15	4	2	87	650	2850	150	180
CNSB145-02X0212	18	4	2	87	650	3050	150	200
CNSB145-03X0207	16	6	3	87	800	2600	150	200
CNSB145-03X0210	23	6	3	87	800	2850	180	220
CNSB145-03X0212	27	6	3	87	800	3050	200	250
CNSB145-03X0307	24	9	3	87	1000	2800	180	250
CNSB145-03X0310	34	9	3	87	1000	3100	220	280
CNSB145-03X0312	41	9	3	87	1000	3300	250	315
CNSB145-04X0307	31	12	4	87	1100	2800	200	280
CNSB145-04X0310	46	12	4	87	1100	3100	250	315
CNSB145-04X0312	55	12	4	87	1100	3300	280	350
CNSB325-02X0207	43	4	2	217	1100	2800	250	315
CNSB325-02X0210	63	4	2	217	1100	3100	300	380
CNSB325-02X0212	75	4	2	217	1100	3300	315	420
CNSB325-03X0207	65	6	3	217	1300	2800	300	380
CNSB325-03X0210	94	6	3	217	1300	3100	350	400x450
CNSB325-03X0212	113	6	3	217	1300	3300	400	400x550
CNSB325-03X0307	98	9	3	217	1800	3150	380	400x450
CNSB325-03X0310	141	9	3	217	1800	3450	450	400x650
CNSB325-03X0312	169	9	3	217	1800	3650	480	400x800
CNSB325-04X0407	173	16	4	217	2400	3650	500	400x800
CNSB325-04X0410	251	16	4	217	2400	3950	600	400x1100
CNSB325-04X0412	300	16	4	217	2400	4150	650	400x1400